

## Fiberglass mesh for render reinforcing

### Description – Fields of application

High-strength fiberglass mesh for reinforcing renders or cement mortars susceptible to cracking.

### Packaging

#### **Blue color, 90 g/m<sup>2</sup>.**

Mesh: 10 mm x 10 mm.

Rolls of 1 m x 50 m (50m<sup>2</sup>) and 0.25 m x 50 m (12.5m<sup>2</sup>).

#### **Blue color, 120 g/m<sup>2</sup>.**

Mesh: 10 mm x 10 mm.

Rolls of 1 m x 50 m (50m<sup>2</sup>).

#### **White color, 90 g/m<sup>2</sup>.**

Mesh: 5 mm x 5 mm.

Rolls of 1 m x 50 m (50m<sup>2</sup>).

#### **White color, 160 g/m<sup>2</sup>.**

Mesh: 4 mm x 4 mm.

Ideal for thermal insulation facades.

Rolls of 1 m x 50 m (50m<sup>2</sup>).

#### **ISOMAT S.A.**

BUILDING CHEMICALS AND MORTARS

#### **MAIN OFFICES - FACTORY:**

17th km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

[www.isomat.eu](http://www.isomat.eu) e-mail: [info@isomat.eu](mailto:info@isomat.eu)