

# ISOMAT COLOR ECONOMY

## Water-based emulsion paint for interior use

### Description

Water-based emulsion paint for interior use. It is characterized by great workability and surface coverage.

### Fields of application

ISOMAT COLOR ECONOMY is recommended for use on new surfaces or surfaces already coated with a water-based emulsion paint, where washing and soiling resistance are not required, such as in ceilings, storage rooms, staircases etc.

### Technical data

Colors:	white and 1330 selected colors (ISOMAT COLOR SYSTEM)
Type:	water-based emulsion paint
Viscosity (Poise):	25-30
Density:	1.68 kg/l
pH:	8.5-9.5 at +23°C
Opacity:	min 90%
Whiteness:	min 65%
Drying Time:	1 h (to the touch)
Recoating in:	3-4 h

Cleaning of tools:  
Tools should be cleaned with water, immediately after use.

### Directions for use

#### 1. Substrate preparation

The substrate should be dry and free of grease, loose particles, dust etc.

- Cracks or joints may be filled with ISOMASTIC-A acrylic sealant.
- Concrete imperfections should be repaired with DUROCRET polymer-modified mortar.
- Plastered wall may be repaired with UNICRET and UNICRET-FAST premixed mortars.
- For puttying surfaces, STUCCOCRET spatula putty should be used.

The surface should be primed with the acrylic, micronized, water-based primer PRIMER CLASSIC, thinned up to 50% with clean water. PRIMER CLASSIC is also ideal to use for the stabilization of the surface, when the substrate is loose or crumbly. Priming is not necessary on already painted surfaces, as long as the old paint is sound.

#### 2. Application

Before using, lightly stir the content and apply in two layers either as it is or thinned by 10-20% with clean water. The second coat is applied thinned by 10-15% with clean water, after the first coat has completely dried. Temperature during application and drying of the color should be between +10°C and +35°C.

### Coverage

ISOMAT COLOR ECONOMY covers 12 m<sup>2</sup>/l, on previously prepared surfaces.

### Packaging

ISOMAT COLOR ECONOMY is supplied in 3 l, 9 l and 15 l containers.

### Shelf-life - Storage

24 months from production date, if stored in original, unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sun exposure and frost.

# ISOMAT COLOR ECONOMY

---

## Volatile Organic Compounds (VOCs)

According to the Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory a, type WB is 30 g/l (2010) for the ready-to-use product.

The ready-to-use product ISOMAT COLOR ECONOMY contains a maximum of 30 g/l VOC.

**ISOMAT S.A.**  
BUILDING CHEMICALS AND MORTARS  
**MAIN OFFICES - FACTORY:**  
17th km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: +30 2310 722 475  
**www.isomat.eu e-mail: info@isomat.eu**

---

The technical information and instructions supplied in this datasheet are based on the knowledge and experience of the Department of Research and Development of our company and on results from long-term applications of the product in practice. The recommendations and suggestions referring to the use of the product are provided without guarantee, since site conditions during the applications are beyond the control of our company. Therefore the user is responsible for confirming that the chosen product is suitable for the envisaged application. The present edition of this technical datasheet automatically cancels any previous one concerning the same product.

