

# ISOMAT ECONOMY COLOR

## Water-based emulsion paint for interior use

### Description

ISOMAT ECONOMY COLOR is a water-based emulsion paint for interior use. Features good opacity and surface coverage while offering great workability and flow. Has quick-drying and recoat times. Almost odorless.

### Fields of application

ISOMAT ECONOMY COLOR is recommended for use on new surfaces or surfaces already coated with a water-based emulsion paint, where washing and soiling resistance are not required, such as ceilings, storage rooms, stairwells, etc.

### Technical data

Colors:	white and thousand of selected colors (ISOMAT COLOR SYSTEM)
Type:	water-based emulsion paint
Viscosity (Poise):	25-30
Density:	1.66±0.03 kg/l
pH:	8,5-9,5 at +23°C
Opacity:	≥ 93% (spreading rate 20 m <sup>2</sup> /l)
Whiteness:	≥ 87%
Drying time:	30-60 min (touch dry)
Recoat time:	3-4 h

#### Cleaning of tools:

Tools should be cleaned with water immediately after use.

### Directions for use

#### 1. Substrate preparation

The substrate should be dry and free of grease, loose particles, dust, etc.

- Cracks or joints may be filled with ISOMASTIC-A acrylic sealant.
- Concrete imperfections should be repaired with DUOCRET polymer-modified mortar.

- Plastered wall can be repaired with UNICRET and UNICRET-FAST premixed mortars.
- For puttying surfaces, STUCCOCRET spatula putty should be used.

The surface should be primed with the acrylic, micronized, water-based primer PRIMER CLASSIC, thinned up to 50% with clean water. PRIMER CLASSIC is also ideal to use for the stabilization of loose or crumbly substrates. In case you are going to paint with dark colors, as an alternative to PRIMER CLASSIC, you can prime the substrate with the acrylic, water-based primer FLEX-PRIMER, tinted in the desired final color. Priming is not necessary on already painted surfaces, as long as the old paint is sound.

#### 2. Application

Before use, gently stir the content and apply in two coats, thinned by 10-20% with clean water. The second coat is applied after the first one has completely dried. Temperature during application and drying of the color should be between +10°C and +35°C.

### Coverage

ISOMAT ECONOMY COLOR covers 10-12 m<sup>2</sup>/l, on previously prepared surfaces.

### Packaging

ISOMAT ECONOMY COLOR is supplied in 3 l, 9 l and 15 l containers.

### Shelf life – Storage

24 months from production date if stored in original, unopened packaging at temperatures between +5°C and +35°C. Protect from direct sunlight and frost.

### Volatile Organic Compounds (VOCs)

According to Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory a, type WB is 30 g/l (2010) for the ready-to-use product.

The ready-to-use product ISOMAT ECONOMY COLOR contains a maximum of 30 g/l VOC.