

ISOMAT GRAFFITI REMOVER

Graffiti remover

Description

ISOMAT GRAFFITI REMOVER is a strong graffiti removal agent that has been formulated to remove graffiti marks from most common types of building surfaces caused by spray paints, markers, etc.

Fields of application

Used for graffiti removal on several surfaces, such as metal, glass, marble, stone, concrete, exposed masonry, etc. Suitable also for use on painted surfaces – tested first on an inconspicuous area.

Technical data

Color: transparent
Density: 1.03 kg/l

Directions for use

Soak a sponge in ISOMAT GRAFFITI REMOVER and softly rub it over the surface wearing protective gloves. Repeat if necessary. Finally, rinse the surface with clean water.

Consumption depends on the graffiti type and the absorbency of the surface.

After cleaning – provided that the surface has completely dried – it is recommended to protect it with ISOMAT AG 80-2K, the special, transparent, polyurethane varnish for protecting surfaces from graffiti. ISOMAT AG 80-2K prevents graffiti paint from penetrating into the substrate and is not affected from the use of ISOMAT GRAFFITI REMOVER. As a result, the surfaces are protected for longer.

Packaging

0.7 l & 4 l containers.

Shelf life – Storage

36 months from production date if stored in original, sealed packaging, in areas protected from high temperatures (<+30°C).

Remarks

- In case ISOMAT GRAFFITI REMOVER is to be used in interior applications, measures for proper ventilation have to be taken.
- Smoking and the use of flame during the application of the product should be avoided.
- Please consult the safety instructions written on the packaging before use.

ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

www.isomat.eu e-mail: support@isomat.eu