

ISOMAT SUPERGRUND

Adhesion primer for roughening smooth or non-absorbent surfaces

Description

ISOMAT SUPERGRUND is an adhesion primer made of synthetic resins and quartz sand. It is applied on smooth and non-absorbent substrates.

- Water-based and thus suitable for interior use, as it is almost odorless.
- Ready-to-use.
- Dries quickly.
- Shows high coverage/hiding power.
- Suitable for substrates with underfloor heating.

Fields of application

ISOMAT SUPERGRUND is used as a ready-to-use primer for roughening the substrate surface, in order to enhance the adhesion of the tile adhesive to be applied.

It is also used as a primer of DUROCRET-DECO, DUROCRET-DECO FLEX, DUROCRET-DECO FINISH decorative microcements and ACRYL DECO FINISH decorative coating.

It is applied on plenty of smooth and non-absorbent substrates, such as old tiles, marble, natural stone, cement-based industrial floorings, wooden, metal or PVC floorings, tarpaulin (linoleum), as well as anhydride and magnesium screeds.

Technical data

Form:	liquid
Color:	red
Density:	1.39 kg/l
Overcoat time:	1 h at +20°C

Directions for use

1. Substrate preparation

The substrate to be primed has to be dry and completely free of dust, oil, and other contaminants.

2. Application

Before use, the content of the container should be well stirred until the mixture becomes homogeneous. In case of non-absorbent substrates, ISOMAT SUPERGRUND is poured directly from the container onto the substrate and spread by roller or brush in one thin layer. If after applying the first layer the surface has not been completely covered with the material, then a second layer should be applied, after the first one has dried.

The adhesive may be applied one hour after priming at +20°C.

In case of absorbent substrates, ISOMAT SUPERGRUND is diluted with pure water at a ratio of up to 1:1, depending on the absorbency of the substrate.

ISOMAT SUPERGRUND may then be uniformly applied on the substrate by roller or brush. The adhesive can be applied after the primer has dried.

DUROCRET-DECO, DUROCRET-DECO FLEX, DUROCRET-DECO FINISH or ACRYL DECO FINISH may be applied after the first 24 hours and as long as the primer has completely dried.

Consumption

100-200 g/m², depending on the absorbency of the substrate.

Packaging

1 kg, 5 kg and 20 kg containers.

Shelf life – Storage

12 months from production date if stored in original unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sunlight and frost.

ISOMAT SUPERGRUND

Remarks

- Temperature during the application should be between +5°C and +30°C.
- The primer should be completely dry before applying the next layer.

Volatile Organic Compounds (VOC)

According to Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory h, type WB is 30 g/l (2010) for the ready-to-use product. The ready-to-use product ISOMAT SUPERGRUND contains a maximum of 30 g/l VOC.

ISOMAT S.A.
BUILDING CHEMICALS AND MORTARS
MAIN OFFICES - FACTORY:
17th km Thessaloniki - Ag. Athanasios
P.O. BOX 1043, 570 03 Ag. Athanasios
Tel. 2310 576 000 Fax: 2310 722 475
www.isomat.eu e-mail: info@isomat.eu

The technical information and instructions supplied in this data sheet are based on the knowledge and experience of the Department of Research and Development of our company and on results from long-term applications of the product in practice. The recommendations and suggestions referring to the use of the product are provided without guarantee, since site conditions during the applications are beyond the control of our company. Therefore, the user is responsible for confirming that the chosen product is suitable for the envisaged application. The present edition of this technical data sheet automatically cancels any previous one concerning the same product.

