

## Fine-grained grout for marbles, with porcelain effect, water-repellent

### Description

MULTIFILL MARBLE 0-3 is a colored, cement based, enriched with resins grout for marbles, granites and tiles. It offers high mechanical strength, superb color stability and great water-repellence. It provides a smooth and glossy final surface. Suitable for joint widths between 0-3 mm.

It is classified as a CG2 WA tile grout, according to EN 13888.

### Fields of application

MULTIFILL MARBLE 0-3 is used for pointing marble, granite, tile and glass mosaic joints, on walls or floors, for indoor and outdoor applications, including swimming pools.

### Technical data

Form:	cementitious powder
Colors:	5
Water demand:	1.30 l/ 4 kg bag
Bulk density of dry mortar:	0.92 ± 0.10 kg/l
Bulk density of fresh mortar:	1.75 ± 0.10 kg/l
Application temperature:	from +5°C to +35°C
Abrasion resistance:	≤ 1000 mm <sup>3</sup>
Compressive strength after:	
• 28 days:	30.00 N/mm <sup>2</sup>
• 25 freeze-thaw cycles:	27.00 N/mm <sup>2</sup>
Flexural strength after:	
• 28 days:	9.00 N/mm <sup>2</sup>
• 25 freeze-thaw cycles:	8.00 N/mm <sup>2</sup>
Drying shrinkage:	≤ 3 mm/m

Water absorption after:

- 30 min: ≤ 2 g
- 240 min: ≤ 5 g

Pot life: 60 min at +20°C

Walkability: after 8-10 h at +20°C

### Directions for use

#### 1. Substrate preparation

The substrate covered with marbles or tiles should be perfectly clean. The joints should be carefully cleaned and dampened with a wet sponge.

#### 2. Application

MULTIFILL MARBLE 0-3 is added to water under continuous stirring, until a uniform paste is formed. A low-speed mixer is recommended for the mixing.

The mixture should be left to settle for about 3 minutes and then slightly stirred again.

Spread the grout on to the joints, using a rubber float in a diagonal direction to the joints, in order to completely fill them. The excess material should be wiped after a while, using a wet sponge. Finally, the surface may be cleaned with a dry cloth.

In case of exterior applications or high temperatures, it is recommended to dampen the joint after a few hours and when the grout has dried.

### Consumption

The consumption of MULTIFILL MARBLE 0-3 depends on the tile dimensions and the joint width. The following cases are mentioned indicatively (values in kg/m<sup>2</sup>):

# MULTIFILL MARBLE 0-3



Tile Dimensions (cm)	Joint width		
	1 mm	2 mm	3 mm
2 x 2 x 0.3	0.40	0.79	1.19
10 x 10 x 0.6	0.16	0.32	0.48
15 x 15 x 0.7	0.12	0.25	0.37
20 x 20 x 0.7	0.09	0.18	0.28
20 x 30 x 0.7	0.08	0.15	0.23
30 x 30 x 0.8	0.07	0.14	0.21

## Packaging - Colors

MULTIFILL MARBLE 0-3 is available in the following 5 colors, with the corresponding code No. and packaging:

Color	4 kg
01 White	•
02 Black	•
05 Light grey	•
06 Bahama beige	•
17 Anemone	•

Sets of realistic MULTIFILL samples are available.

## Shelf-life - Storage

24 months from production date, if the product is stored in original unopened packaging, in places protected from moisture and frost.

## Remarks

- MULTIFILL MARBLE 0-3 contains cement that reacts with moisture forming alkaline solutions, so it is classified as irritant.
- Consult the directions for safe use and precautions written on the package.

## ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

### MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

[www.isomat.net](http://www.isomat.net) e-mail: [info@isomat.net](mailto:info@isomat.net)

The technical information and instructions supplied in this datasheet are based on the knowledge and experience of the Department of Research and Development of our company and on results from long-term applications of the product in practice. The recommendations and suggestions referring to the use of the product are provided without guarantee, since site conditions during the applications are beyond the control of our company. Therefore the user is responsible for confirming that the chosen product is suitable for the envisaged application. The present edition of this technical datasheet automatically cancels any previous one concerning the same product.

