

Ready-to-use, lightweight acrylic spackling putty

Description

FAST-COVER is a ready-to-use acrylic spackling putty for fast filling and patching of cracks, crevices or holes with a single-step application. It can be painted after 30 min.

Fields of application

FAST-COVER is applied on porous surfaces such as plaster, gypsum board or other drywall structures, wood, etc. in thickness of up to 5 cm. It does not crack and it does not need sanding.

Technical data

Color:	white
Density:	0,36 kg/lit
Application temperature:	from +5°C to +35°C
Painting:	after 30 min

Directions for use

1. Substrate

The cracks or holes are thoroughly cleaned (wiped, brushed etc.) in order to prepare a substrate free of dust, grease, loose particles etc. Before application, the material is well stirred until a pasty mix comes up.

2. Application

The putty is applied with a putty knife on the desired spot and it is pressed to fill completely the void space. The surface is smoothed out with the putty knife. After drying of the repaired surface (in approx. 30 minutes), painting can follow.

Packaging

FAST-COVER is supplied in plastic containers of 0,5 lit, 1 lit and 5 lit.

Shelf-life - Storage

12 months from production date if stored in original, unopened packaging, in temperature between +5°C and +35°C. Protect from direct sun exposure and frost.

Volatile organic compounds (VOCs)

According to the Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory g, type WB is 30g/l (2010) for the ready to use product.

The ready to use product FAST-COVER contains max <30 g/l VOC.

ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

www.isomat.net e-mail: info@isomat.net