

Primer of brushable elastomeric waterproofing membranes

Description

Aqueous polymer emulsion. It ensures the proper adhesion of the brushable, elastomeric membranes ISOFLEX and ISOFLEX-T25, when waterproofing terraces with porous substrates. By penetrating inside the pores of the substrate, it acts as a bonding layer between ISOFLEX or ISOFLEX-T25 and the substrate.

Fields of application

ISO-PRIMER is used as a primer for securing the adhesion of ISOFLEX and ISOFLEX-T25 on substrates like concrete, masonry, plaster, gypsum boards, chip boards etc.

Technical data

Form: emulsion
 Color: white
 Density: 1,01 kg/lit

Directions for use

1. Substrate

The surface to be primed must be dry and free of dust, grease, dirt etc.

2. Application

ISO-PRIMER is thoroughly stirred and applied uniformly on the substrate by brush, roller or spraying, before the application of the brushable elastomeric liquid membranes.

Consumption

200-300 g/m², depending on the absorptivity of the substrate.

Packaging

ISO-PRIMER is available in plastic containers of 1 kg, 5 kg and 20 kg.

Shelf-life - Storage

12 months from production date if stored in original, unopened packaging, in temperature between +5°C and +35°C. Protect from direct sun exposure and frost.

Remarks

- Temperature during the application should be at least +5°C.

Volatile organic compounds (VOCs)

According to the Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory h, type WB is 30g/l (2010) for the ready to use product.

The ready to use product ISO-PRIMER contains max <30 g/l VOC.

ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,
 P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
 Tel.: +30 2310 576 000, Fax: +30 2310 722 475

www.isomat.net e-mail: info@isomat.net