

## Bituminous mastic

### Description

Bituminous sealing mastic with excellent adhesion ability and great elasticity even at very low temperatures.

### Fields of application

It is used for sealing joints on horizontal and vertical surfaces, for sealing/bridging hairline cracks, difficult points during application of bituminous membranes (gutters, joints, parapet finishings etc). Also used for repairing bituminous layers.

### Technical data

Form: viscous, gluey  
Color: black  
Specific weight: 1,40 kg/lit  
Distilled residue: 80-85%  
Cleaning of tools:  
Tools must be cleaned thoroughly immediately after use with petrol or a solvent.

### Directions for use

ISOMAC is cold-applied with a trowel as it is. For lengthy horizontal joints it may be diluted with petrol and applied by injecting directly from the container.

Mastic starts to settle after 24 hours. Loss of mass, occurring as a result of solvent evaporation, is supplemented by the same material the day after the initial application.

### Consumption

1,2-1,3 kg/lit.

### Packaging

5 kg and 20 kg tin buckets.

### Shelf-life - Storage

12 months from the date of production in sealed containers, in cool, dry and frost-free conditions.

### Volatile organic compounds (VOCs)

According to the Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory g, type SB is 350g/l (2010) for the ready to use product.

The ready to use product ISOMAC contains max <350 g/l VOC.

**ISOMAT S.A.**  
BUILDING CHEMICALS AND MORTARS  
**MAIN OFFICES - FACTORY:**  
17th km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: +30 2310 722 475  
**www.isomat.net e-mail: info@isomat.net**