

Roofing membrane for ventilated roofs

Description	Technical data
<p>The waterproofing membrane ROOF-TOP is suitable to be placed on ventilated (cold) roofs onto the sheeting. Alternatively, it can be used on cold roofs without sheeting. In that occasion the membrane should be placed onto the rafters or the counter battens that encompass the thermal insulation, tensioned or to form a slight sag. The membrane is used also for (cold) roofs made of reinforced concrete and is placed onto the counter battens.</p> <p>The waterproofing membrane is consisted from a layer of oxidized bitumen that forms the absolute hydro-insulation against water, snow and humidity and is double covered of perforated polyethylene film.</p> <p>The membrane is having minimum vapor permeability ($S_d > 100$ m) due to its bituminous composition, so is recommended that the unions of successive leaves are not stamped in order to allow vapor but not water to pass through. Moreover, the membrane is very easy mounted without danger of tearing because of the low weight and great mechanical strength.</p> <p>In case of a vapor-barrier is necessary it is recommended the usage of the roofing membrane DELTA-REFLEX.</p>	<p>Material: 3 layers - Polyester reinforcement and double cover of perforated polyethylene film</p> <p>Reinforcement: polyester</p> <p>Mechanical strength:</p> <ul style="list-style-type: none"> • by length: 500 N/5 cm • by width: 300 N/5 cm <p>Impermeability: waterproofing membrane</p> <p>Vapor-permeability: $S_d > 100$ m</p> <p>Resistance to temperature changes: -40°C up to $+80^{\circ}\text{C}$</p> <p>Weight: 800 gr/m²</p>
	Packaging
	<p>Rolls of 1m x 30m (30 m²) each.</p>

ISOMAT S.A.
 BUILDING CHEMICALS AND MORTARS
MAIN OFFICES - FACTORY:
 17th km Thessaloniki - Ag. Athanasios Road,
 P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
 Tel.: +30 2310 576 000, Fax: +30 2310 722 475
www.isomat.net e-mail: info@isomat.net