

## Adhesion primer for silicone plasters

### Description

Silicone polymer emulsion which stabilizes porous substrates and ensures the proper adhesion of silicone plasters.

By penetrating inside the pores of the substrate, it acts as a bonding layer between the substrate and the plaster, to be applied.

### Fields of application

SILICONE-PRIMER is ready-to-use primer, applied on porous substrates made of concrete, masonry, plaster, gypsum boards, chip boards etc.

It stabilizes weak or crumbling plasters etc. Used in combination with MARMOCRYL SILICONE plasters, it forms an ideal system for the covering and decoration of walls.

### Technical data

Form:	emulsion
Color:	white
Density:	1,00 kg/lit

### Directions for use

#### 1. Substrate

The surface to be primed must be dry and free of dust, grease, dirt etc.

SILICONE PRIMER is thoroughly stirred and uniformly applied on the substrate by brush or roller. After has been dried, follows the application of MARMOCRYL SILICONE plaster.

### Consumption

100-200 g/m<sup>2</sup>, depending on the absorptivity of the substrate.

### Packaging

SILICONE-PRIMER is available in plastic containers of 5 kg, 10 kg and 20 kg.

### Shelf-life - Storage

12 months from production date if stored in original, unopened packaging, in temperature between +5°C and +35°C. Protect from direct sun exposure and frost.

### Remarks

Temperature during application should be at least +5°C.

### Volatile organic compounds (VOCs)

According to the Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory h, type WB is 30g/l (2010) for the ready to use product.

The ready to use product SILICONE-PRIMER contains max <30 g/l VOC.

#### ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

#### MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

[www.isomat.net](http://www.isomat.net) e-mail: [info@isomat.net](mailto:info@isomat.net)

## 2. Application

The technical information and instructions supplied in this datasheet are based on the knowledge and experience of the Department of Research and Development of our company and on results from long-term applications of the product in practice. The recommendations and suggestions referring to the use of the product are provided without guarantee, since site conditions during the applications are beyond the control of our company. Therefore the user is responsible for confirming that the chosen product is suitable for the envisaged application. The present edition of this technical datasheet automatically cancels any previous one concerning the same product.

