

Special solvent for epoxy systems

Description

SM-12 is a liquid mixture of solvents that is used as a tool cleaner in applications of a wide range of epoxy systems and other kinds of resins.

Fields of application

SM-12 is used in applications of epoxy coatings, paints etc.

Technical data

Color: transparent

Density: 0,80 kg/lit

Directions for use

SM-12 is used undiluted for cleaning of tools from epoxy resin residues and mixed with water at ratios of up to 1:1 (by volume) for cleaning of tools from water-based paint residues.

Consumption

Consumption varies depending on the nature of the application.

Packaging

SM-12 is supplied in plastic containers of 5 lit.

Storage

Shelf-life in sealed containers is 36 months, protected from high temperature (<+30°C).

Remarks

- Consult the safety advice and precautions written on the label and on the product's material safety data sheet.
- In cases of application in closed areas, measures for good ventilation should be taken.
- The product is classified as highly flammable and therefore smoking and use of flame should be avoided in the working area during use.

ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

www.isomat.net e-mail: info@isomat.net