

Special solvent for epoxy coatings

Description

SM-14 is a mixture of solvents used for diluting (thinning) epoxy coatings.

Fields of application

SM-14 is used for diluting EPOXYCOAT, EPOXYCOAT-S, EPOXYCOAT-AC epoxy coatings and for cleaning of tools after working with such materials.

Technical data

Color: transparent
Density: 0,85 kg/lit

Directions for use

SM-14 is used for diluting epoxy coatings when added in portions up to 10%. It may also be used for removing epoxy coating residues from tools.

Consumption

Consumption varies depending on the nature of the application.

Packaging

5 lit containers.

Shelf-life - Storage

Shelf-life in sealed containers is 36 months, protected from high temperature (<+30°C).

Remarks

- When applying SM-14 in closed areas, care should be taken for proper ventilation.
- Smoking and use of flame should be avoided during application.
- Before use, read safety instructions on the product label.

ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

www.isomat.net e-mail: info@isomat.net