

Special solvent for polyurethane coatings

Description

SM-16 is a solvent used for diluting (thinning) polyurethane coatings.

Fields of application

SM-16 is used for diluting the brushable polyurethane waterproofing membrane ISOFLEX-PU, especially when it is going to be applied by spraying, and also for cleaning the tools used for the application of ISOFLEX-PU. Furthermore SM-16 can clean the tools from epoxy coatings residues and can be used as a thinner for epoxy coatings.

Technical data

Color: transparent
Density: 0,87 kg/l

Directions for use

SM-16 is used for diluting polyurethane coatings when added in portions up to 10%.

Consumption

Consumption varies depending on the nature of the application.

Packaging

5 l containers.

Shelf-life - Storage

Shelf-life in sealed containers is 36 months, protected from high temperature (<+30°C).

Remarks

- When applying SM-16 in closed areas, care should be taken for proper ventilation.
- Smoking and use of flame should be avoided during application.
- Before use, read safety instructions on the product label.

ISOMAT S.A.
BUILDING CHEMICALS AND MORTARS
MAIN OFFICES - FACTORY:
17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 722 475
www.isomat.net e-mail: info@isomat.net