

Special solvent for PRIMER ACRYL-S

Description

SM-18 is a mixture of solvents with a distinctive smell.

Fields of application

SM-18 is used for diluting PRIMER ACRYL-S. Furthermore SM-18 is suitable for diluting solvent based lacquers and varnishes for application by brush or roller and for cleaning of tools after working with such materials.

Technical data

Color: transparent

Density: 0,79 kg/l

Directions for use

SM-18 is used for diluting the acrylic primer PRIMER ACRYL-S in portions up to 100% by weight.

Consumption

Consumption varies depending on the nature of the application.

Packaging

0,75 l, 5 l and 20 l containers.

Shelf-life - Storage

Shelf-life in sealed containers is 36 months, protected from high temperature (<+30°C).

Remarks

- When applying SM-18 in closed areas, care should be taken for proper ventilation.
- Smoking and use of flame should be avoided during application.
- Before use, read safety instructions on the product label.

ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

www.isomat.net e-mail: info@isomat.net