

SPLIT-2000

Formwork deshuttering agent

Description

SPLIT-2000 is a deshuttering coating for all types of wood or metal formworks, acting in a physical way by forming an adhesion-preventing film on the concrete surface, as well as in a chemical way by reacting with the concrete surface. It offers the following advantages:

- A strong anti-adhesive action.
- No air-bubbles are formed on the concrete surface.
- Avoidance of oil or grease residues on the concrete surface.
- Perfect bonding of plaster or paint on the concrete surface.
- Low-cost, due to low consumption.
- Protection of metal formworks from corrosion and maintenance of wood formworks.

Fields of application

SPLIT-2000 is used as an anti-adhesive coat on any type of wood or metal formwork. It is ideal to achieve smooth surfaces of exposed concrete.

Technical data

Color: dark yellow

Density: 0,86 kg/lit

Directions for use

SPLIT-2000 should be thoroughly stirred before use. It is applied without any dilution, by brush or spray, on a clean and dry formwork surface, wood or metal, in one layer as thin as possible.

Consumption

Approx. 60 ml/m², according to the type and absorptivity of the coated surface.

Packaging

SPLIT-2000 is supplied in plastic containers of 20 lit and drums of 140 lit.

Shelf-life - Storage

18 months from production date if stored in original, unopened packaging, in temperature between +5°C and +35°C. Protect from direct sun exposure and frost.

ISOMAT S.A.
BUILDING CHEMICALS AND MORTARS
MAIN OFFICES - FACTORY:
17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 722 475
www.isomat.net e-mail: info@isomat.net