

## Technical Datasheet

# CL-MARBLE

## Cleaner for marbles and granites

### Description

Special liquid cleaner for marbles and granites. CL-MARBLE removes the stains, without affecting the shine of the marbles or granites.

### Fields of application

CL-MARBLE is used to coffee, wine, oil, nicotine, soot and other stains from marbles and granites. It does not contain acids and does not affect sensitive surfaces.

### Technical data

Form : liquid  
pH : 6.5-7.5

### Directions for use

CL-MARBLE is applied undiluted on the stained surface and is left there until the stain dissolves and disappears. It usually takes 24 hours until a stain is completely removed. During the application, it might be necessary to add some more quantity. For difficult stains, repeat the same process.

### Consumption

15-20m<sup>2</sup>/l, depending on the stain.

0.75 l, 5 l and 20 l containers.

### Storage

12 months from production date, if stored in original, unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sun exposure and frost.

### Remarks

- Consult the directions for safe use and precautions written on the package.
- Harmful if swallowed. Risk of serious damage to eyes. Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear eye/face protection.
- It contains more than 15% (but less than 30%) of bleaching agent based on oxygen. It also contains methylchloroisothiazolinone, methylisothiazolinone and perfume.

**ISOMAT S.A.**  
BUILDING CHEMICALS AND MORTARS  
**MAIN OFFICES - FACTORY:**  
17th km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: +30 2310 722 475  
[www.isomat.eu](http://www.isomat.eu) e-mail: [info@isomat.eu](mailto:info@isomat.eu)

### Packaging

The technical information and instructions supplied in this datasheet are based on the knowledge and experience of the Department of Research and Development of our company and on results from long-term applications of the product in practice. The recommendations and suggestions referring to the use of the product are provided without guarantee, since site conditions during the applications are beyond the control of our company. Therefore the user is responsible for confirming that the chosen product is suitable for the envisaged application. The present edition of this technical datasheet automatically cancels any previous one concerning the same product.

