

SM-28

Special solvent for polyurethane-based products

Description

SM-28 is a specially formulated solvent blend of aromatic hydrocarbons and esters, used in combination with polyurethane-based products.

Fields of application

Specifically designed for thinning polyurethane-based products (paints, liquid waterproofing membranes, etc.), especially when applied by spray. Also effective for cleaning application tools. Thanks to its special formulation, SM-28 allows for quick drying of the polyurethane material.

Technical data

Color: clear / colorless
Density: 0.86 ± 0.02 kg/l

Directions for use

SM-28 is used for thinning polyurethane materials at a ratio of up to 10% by weight.

Consumption

Consumption varies depending on the nature of the application.

Packaging

0.75 l & 4 l containers.

Shelf life – Storage

36 months from production date, in original, sealed containers, stored at temperatures above 5°C and protected from high temperatures (<+30°C).

Remarks

- Ensure adequate ventilation when applying SM-28 indoors.
- Keep away from sources of ignition during application – No smoking.
- Please consult the directions for safe use and precautions written on the packaging before use.
- For further information, please refer to the Material Safety Data Sheet.

ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 57 029

www.isomat.eu e-mail: support@isomat.eu