

Technical Datasheet

FIBERGLASS FLEECE GF 50 TR**Fiberglass fleece for reinforcing waterproofing layers 50 g/m²****Description – Fields of application**

Fiberglass fleece 50 g/m², used for local and total reinforcement of the transparent polyurethane liquid waterproofing membrane ISOFLEX-PU 650 in case of local cracks, at wall-floor junctions, corners, etc.

FIBERGLASS FLEECE GF 50 TR looks transparent after its complete embedment in ISOFLEX-PU 650, especially when applied to solid surfaces such as ceramic tiles, natural stone, wood, etc.

Technical data

| | |
|-----------|---------------------------|
| Material: | glass fibers |
| Weight: | 50 g/m ² ± 5 % |
| Color: | white translucent |

Packaging

1.03 m x 100 m rolls (103 m²).

Storage

Stored in its original, sealed packaging, protected from humidity and UV radiation.

Remarks

The use of FIBERGLASS FLEECE GF 50 TR affects the clarity of the final surface; a test application is recommended prior to use on completely transparent substrates made of pure glass or polycarbonate sheets.

ISOMAT S.A.
BUILDING CHEMICALS AND MORTARS
HEADQUARTERS – FACTORY:
17th km Thessaloniki - Ag. Athanasios
P.O. BOX 1043, 570 03 Ag. Athanasios
Tel.: 2310 576 002, Fax: +30 2310 576 029
www.isomat.eu e-mail: support@isomat.eu